



USE AND CARE INSTRUCTIONS FOR YOUR NEW PENNTEK FLOOR

WHEN THE INSTALL IS COMPLETE:

- Do not close the garage door until the morning after installation.
- Please allow a minimum of 6-8 hours before walking on, depending upon humidity. Waiting until the next morning is ideal.
- You may drive on the floor 24 hours after installation is complete, again depending on humidity. Waiting 36-48 hours is ideal. The floor will reach full chemical resistance at 72 hours of cure time.

ONGOING MAINTENANCE:

- You will be happy to know that your floor is easy to maintain!
- Sweep off sand and salt, then rinse with water. A squeegee works great to clear water off.
- Ask your dealer about Penntek's LGX-501 floor cleaner. This solvent-based cleaner has been designed specifically to work with Penntek Coatings. The liquid concentrate will make your floors sparkling clean when mixed with warm water.
- If you prefer, you may use your favorite floor cleaner to manufacturers specifications. We recommend Simple Green, Pine-Sol, CLR, and Dawn. Avoid long-term bleach exposure and avoid acids and highly corrosive materials.
- For tougher cleaning, let the cleaner sit on the floor for 5-10 minutes and scrub with a scrub brush or stiff bristle broom. Wait an additional five minutes followed by a rinse for a revitalized floor.